

# PRODUCT SPECIFICATIONS FOR P450-3

## GENERATOR SET SPECIFICATIONS

---

<b>Minimum Rating</b>	400 kVA / 320 kW
<b>Maximum Rating</b>	450 kVA / 360 kW
<b>Emissions/Fuel Strategy</b>	Fuel Optimised
<b>50 Hz Prime</b>	400 kVA / 320 kW
<b>50 Hz Standby</b>	450 kVA / 360 kW
<b>Frequency</b>	50 Hz
<b>Speed</b>	1500 RPM
<b>Voltage</b>	220-415 Volts

## ENGINE SPECIFICATIONS

---

<b>Engine Model</b>	Perkins® 2206A-E13TAG3
<b>Bore</b>	130 mm (5.1 in)
<b>Stroke</b>	157.0mm (6.2 in)
<b>Governor Type</b>	Electronic
<b>Displacement</b>	12.5l (762.8 cu. in)
<b>Compression Ratio</b>	16.3:1

## P450-3 STANDARD EQUIPMENT

### ENGINE

- Air Cleaner
- Lube oil drain valve
- Engine filled with lubrication oil
- High Coolant Temperature Shutdown
- Low Oil Pressure Shutdown
- Engine mounted battery charging alternator

### COOLING

- Package mounted radiator
- Radiator fan and charging alternator guards

- Coolant Drain Valve
- Cooling System filled with Coolant mix

## **EXHAUST**

- Exhaust flange outlet
- Exhaust bellows and gasket

## **FUEL**

- 8 Hr Fuel Tank
- BSP Fuel Sockets

## **ALTERNATOR**

- FG Wilson
- SHUNT Excitation
- IP21 Protection

## **CONTROL PANEL**

- PowerWizard 1.1+

## **MOUNTING**

- Robust steel constructed base frame
- Base frame drag and lift points
- Captive linear vibration isolators between base and engine-generator
- Battery Tray and Cables

# **P450-3 OPTIONAL EQUIPMENT**

## **EXHAUST**

- Industrial, Residential, Critical Silencers

## **ALTERNATOR**

- Quadrature Droop Kit (AR6)
- Anti-Condensation Heater and Panel Circuitry (AH1)
- AREP / PMG excitation

- AVR Upgrades
- Three phase sensing
- Oversize Alternator
- Coastal ingress protection alternator
- Leroy Somer Alternator

## **CONTROL PANELS**

- PowerWizard 2.1
- easYgen-2500

## **STARTING/CHARGING**

- Heavy duty dry battery
- Battery charger with auto boost

## **GENERAL**

- Upgrade to Standard Set for "CE" Certification
- EEC Declaration of Conformity
- Dual wall base tank (8 hrs)
- Sound attenuated or High ambient enclosures
- Battery isolator switch

## **ENCLOSURE**

- Compliance to European Community Directive 2000/14/EC
- Super sound attenuation for residential areas
- Totally enclosed exhaust silencing system
- 50°C High ambient capability available
- Robust and highly corrosion resistant construction